



产品 手 册

仪器型号: SRS斯坦福前置放大器SR445A

西安安泰测试科技有限公司

仪器维修|租赁|销售|测试

地址:西安市高新区纬二十六路 369 号 网址: <u>www.agitekservice.com</u> 电话:400-876-5512 座机:029-88827159

350 MHz Preamplifier

SR445A — 350 MHz preamplifier (4-channel)



The Model SR445A 350 MHz Preamplifier contains four wide-bandwidth, DC-coupled amplifiers, each with a gain of 5. The four channels may be used independently, or cascaded to provide a total gain of up to 625. The fast rise time, low noise, and excellent DC accuracy of the SR445A make it an ideal instrument for amplifying the outputs of fast photomultiplier tubes and photodiodes. The SR445A can be used to improve the sensitivity of oscilloscopes, photon counters, boxcar averagers, spectrum analyzers, and other high-frequency test equipment.

Each channel has an input and output impedance of 50Ω . The input impedance of channel one can be increased to approximately 500Ω by a front-panel switch. This can improve the sensitivity of signals from current and charge output devices, such as photomultiplier tubes. Each channel has a separate offset adjustment allowing you to quickly null DC errors.

· Four independent channels

- · DC to 350 MHz bandwidth
- · 1 ns rise and fall time
- · Voltage gain to 625
- \cdot 6.4 nV/ $\sqrt{\text{Hz}}$ input noise
- \cdot 50 Ω input and output impedance
- · 3 ns overload recovery
- · Excellent phase linearity

SR445A Specifications

Amplifier channels	4	
Inputs and outputs	50 Ω , DC coupled	
Bandwidth	DC to 350 MHz (-3 dB)	
Rise/fall time	1 ns (single channel)	
Voltage gain	5 per channel	
	(Up to 4 channels can be cascaded.)	
Input noise	$6.4 \mathrm{nV}/\sqrt{\mathrm{Hz}}$	
Operating range	Inputs: $\pm 200 \text{mV}$, Outputs: $\pm 1.0 \text{V}$	
Propagation delay	2.7 ns per channel	
Recovery time	$3 \text{ ns for a } 10 \times \text{ overload}$	
Input protection	$\pm 50 V$ for $<1 \mu s$	
Output clamp	±1.6 V	
Output overload detect	$\pm 1.3 \mathrm{V}$	
Crosstalk	-60 dB	
Operating temperature	0°C to 40°C, non-condensing	
Dimensions	8.3"×1.5"×8" (WHD)	
Power	10W, 100/120/220/240VAC,	
	50/60 Hz	
Warranty	One year parts and labor on defects	
	in materials and workmanship	

Ordering Information

SR445A	350 MHz preamplifier	\$1395



· SR445A ... \$1395 (U.S. list)

phone: (408)744-9040 www.thinkSRS.com