



# 产 品 手 册

仪器型号：BONN射频功率放大器BLWA\_0830-200D

西安安泰测试科技有限公司

仪器维修|租赁|销售|测试

地址:西安市高新区纬二十六路 369 号

网址: [www.agitekservice.com](http://www.agitekservice.com)

电话: 400-876-5512

座机: 029-88827159

## STANDARD MODELS

| Model          | Frequency Range   | Output Power<br>$P_N$ min / typ<br>W | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|----------------|-------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BLWA 0830-200D | 80 ... 3000 MHz   |                                      |                         |                               | 1800             | 8 HU, 630 mm                       | 72           |
|                | 80 ... 1000 MHz   | 200 / 250                            | 53 / 55 ±2              | 20 / 20                       |                  |                                    |              |
|                | 1000 ... 3000 MHz | 200 / 220                            | 53 / 55 ±2              | 15 / 20                       |                  |                                    |              |

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

|                       |                                                 |
|-----------------------|-------------------------------------------------|
| Input Power:          | 0 dBm (1 mW) max.                               |
| Overdrive Protection: | up to +10 dBm for no damage                     |
| Input Impedance:      | 50 Ohm nominal                                  |
| Output Impedance:     | 50 Ohm nominal                                  |
| Input VSWR:           | <2:1 typ.                                       |
| Load VSWR:            | infinite for no damage (100% mismatch tolerant) |
|                       | $P_N$ -0.5 dB min. at VSWR 2:1                  |
| Spurious (at $P_N$ ): | -60 dBc min. (excluding harmonics)              |
| Class of Operation:   | A-linear or AB-linear                           |

## GENERAL

|                      |                                            |
|----------------------|--------------------------------------------|
| RF Input:            | N-f, standard on rear panel                |
| RF Output:           | N-f, standard on rear panel                |
| Mains Supply:        | 200 ... 240 V AC ±10%, 47 ... 63 Hz        |
| Elapsed Time Meter:  | via status display                         |
| Ambient Temperature: | 0 ... +45 °C                               |
| Storage Temperature: | -20 ... +85 °C                             |
| Relative Humidity:   | up to 95% (non-condensing)                 |
| Operating Altitude:  | up to 2000 m above sea level               |
| Vibration and Shock: | MIL-STD-810 G                              |
| Cooling:             | forced air with integral blower            |
|                      | air intake from front, air exhaust at rear |

## OPTIONS

|                                      |                                  |
|--------------------------------------|----------------------------------|
| A) RF-Sample Ports                   | I) 3x 208 V AC / 60 Hz           |
| B) External Dual Directional Coupler | L) LAN Remote Control            |
| C) IEEE-488.2 GPIB Remote Control    | S) Internal RF Switching Unit    |
| D) Front Panel RF Connectors         | R) RS-232C/RS-485 Remote Control |
| E) RF Power Indication (digital)     | U) USB Remote Control            |
| F) Gain Adjustment                   | W) Liquid Cooling                |

## BLWA 80 ... 3000 MHz Solid State Amplifiers

H) DC Supply

X) External Control of other Amplifiers