# PXI-2567 Specifications

2025-03-14

n

## Contents

PXI-2567 Specifications
-------------------------

## PXI-2567 Specifications

**Caution** The protection provided by the PXI-2567 can be impaired if it is used in a manner not described in this document.

#### Definitions

*Warranted* specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

*Characteristics* describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the performance met by a majority of models.
- **Nominal** specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are *Typical* unless otherwise noted.

## Conditions

Specifications are valid at 23 °C unless otherwise noted.

All voltages are specified in DC, AC<sub>pk</sub>, or a combination unless otherwise specified.

## Topology

Topology Independ	dent
-------------------	------

## Input<sup>[1]</sup>

Maximum drive voltage, external power		50 V DC
Maximum drive current		
Per channel	600 mA	
Per module	25 A	
Internal drive power <sup>[2]</sup>		5 V at 1.25 A 12 V at 0.5 A

## Dynamic

Single-channel operate time <sup>[3][4]</sup> at 25 °C		60 μs, typical	
Channel-to-ground resistance (RDSon)			
0 mA to 600 mA drive current		0.280 Ω, maximum	
Channel off drain current (IDSS)			
13 V drive voltage	50 μ <i>i</i>	A, typical	
25 V drive voltage	200 µ	ıA, typical	

## Trigger

Input trigger		
Sources		PXI trigger lines <07>
Minimum pulse width <sup>[5]</sup>		150 ns
Front panel/terminal block input voltage		-0.5 V, minimum +0.7 V, VL maximum +2.0 V, VH minimum +3.3 V, nominal +5.5 V, maximum
Output trigger		
Destinations	PXI trigger lines <07>	
Pulse width	Software-selectable: 1 μs to 62 μs	
Front panel voltage	3.3 V TTL, 8 mA, nominal	

## Physical

I/O connector	78-pin D-SUB	
PXI power requirement, including optional internal drive power		

5 V		8 W
3.3 V		0.5 W
12 V		6 W
Dimensions (L × W × H)	3U, one slot, PXI/cPCI module 21.6 × 2.0 × 13.0 cm (8.5 × 0.8 × 5.1 in.)	
Weight	220 g (8 oz)	

## Environment

Operating temperature	0 °C to 55 °C
Storage temperature	-20 °C to 70 °C
Relative humidity	5% to 85%, noncondensing
Pollution Degree	2
Maximum altitude	2,000 m

Indoor use only.

#### **Shock and Vibration**

Operational Shock	30 g peak, half-sine, 11 ms pulse (Tested in accordance with IEC 60068-2-27. Test profile developed in accordance with MIL-PRF-28800F.)
Random Vibr	ation
Operating	5 Hz to 500 Hz, 0.3 g <sub>rms</sub>
Nonoperating	5 Hz to 500 Hz, 2.4 g <sub>rms</sub> (Tested in accordance with IEC 60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.)

## **Compliance and Certifications**

#### **Safety Compliance Standards**

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1

**Note** For safety certifications, refer to the product label or the <u>Product</u> <u>Certifications and Declarations</u> section.

#### **Electromagnetic Compatibility**

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity

- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions

**Note** In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.

**Note** Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.

**Note** For EMC declarations, certifications, and additional information, refer to the <u>Product Certifications and Declarations</u> section.

#### **Product Certifications and Declarations**

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit <u>ni.com/product-certifications</u>, search by model number, and click the appropriate link.

#### **Environmental Management**

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the **Engineering a Healthy Planet** web page at <u>ni.com/environment</u>. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document. EU and UK Customers

• X Waste Electrical and Electronic Equipment (WEEE)—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit <u>ni.com/environment/weee</u>.

电子信息产品污染控制管理办法(中国RoHS)

 ●●●●中国RoHS-NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息,请登录ni.com/environment/ rohs\_china。(For information about China RoHS compliance, go to ni.com/ environment/rohs china.)