

---

# PXle-2737

# Specifications

---

2025-03-13



# Contents

PXIe-2737 Specifications ..... 3

# PXle-2737 Specifications


This document lists specifications for the PXle-2737 . All specifications are subject to change without notice.

## PXle-2737 Specifications

**Specifications** characterize the warranted performance of the instrument under the stated operating conditions. Data in this document are **Specifications** unless otherwise noted.

**Typical Specifications** are specifications met by the majority of the instrument under the stated operating conditions and are tested at 23 °C ambient temperature. Typical specifications are not warranted.

All voltages are specified in DC, AC<sub>pk</sub>, or a combination unless otherwise specified.

**Caution** The protection provided by the PXle-2737 can be impaired if it is used in a manner not described in this document.

## Topology

Topology	2-wire 4 × 64 matrix
----------	----------------------

## Input Characteristics

Maximum switching voltage	
Channel-to-channel	100 V

Channel-to-ground	100 V, CAT O
-------------------	--------------



**Note** This module is rated for Measurement Category I. It is intended to carry signal voltages no greater than 70 V<sub>rms</sub>, 100 V<sub>pk</sub>, or 100 VDC. This module can withstand up to 500 V impulse voltage. Do not use this module for connection to signals or for measurements within Categories II, III, or IV. Do not connect to MAINS supply circuits (for example, wall outlets) of 115 VAC or 230 VAC.

Measurement Categories CAT I and CAT O (Other) are equivalent and are for measurements performed on circuits not directly connected to the electrical distribution system referred to as MAINS voltage. This category is for measurement of voltages from specially protected secondary circuits. Such voltage measurements include signal levels, special hardware, limited-energy parts of hardware, circuits powered by regulated low-voltage sources, and electronics.



**Caution** When hazardous voltages (>42.4 Vpk/60 V DC) are present on any channel, safety low-voltage (≤42.4 Vpk/60 V DC) cannot be connected to any other channel.

Maximum switching power	60 W, 62.5 VA
-------------------------	---------------



**Caution** The switching power is limited by the maximum switching current, the maximum voltage, and must not exceed 60 W, 62.5 VA.

Maximum current	
Switching	2 A (per channel)
Carry	2 A (per channel)

Minimum switching load	20 mV/1 mA
------------------------	------------



**Note** Switching inductive loads (for example, motors and solenoids) can produce high voltage transients in excess of the module's rated voltage. Without additional protection, these transients can interfere with module operation and impact relay life. For more information about transient suppression, visit [ni.com/info](http://ni.com/info) and enter the Info Code `relayflyback`.

DC isolation resistance (channel-to-COM)	1 G $\Omega$ (typical at 25° C)
<b>DC path resistance</b>	
Initial	<1.3 $\Omega$ , warranted
End-of-life	$\geq 2.3 \Omega$

Path resistance is a combination of relay contact resistance and trace resistance. Measure path resistance by combining resistance of the high and low signal paths from one row to one column. Contact resistance typically remains low for the life of a relay. At the end of relay life, the contact resistance rises rapidly above  $\geq 2.3 \Omega$ .

Thermal EMF	<10 $\mu$ V
-------------	-------------

## RF Performance Characteristics

<b>Bandwidth (-3 dB, typical at 23° C)</b>	
1-wire 50 $\Omega$ termination	$\leq 10$ MHz

2-wire 100 Ω termination		≤ 10 MHz
Open channel isolation (typical at 23° C, 50 Ω termination )		
10 kHz	≥ 81 dB	
100 kHz	≥ 61 dB	
1 MHz	≥ 41 dB	
Channel-to-channel crosstalk (typical at 23° C, 50 Ω termination )		
10 kHz	≤ -67 dB	
100 kHz	≤ -50 dB	
1 MHz	≤ -32 dB	

## Dynamic Characteristics

<b>Relay Operate Time</b>		
Typical	1 ms	
Maximum	3.3 ms	
Simultaneous drive limit	90 relays	

Expected mechanical relay life	$1 \times 10^8$ cycles
<b>Expected electrical relay life</b>	
$\leq 30$ mV, $\leq 10$ mA resistive	$2.5 \times 10^6$ cycles
30 V, 1 A	$5 \times 10^5$ cycles
30 V, 2 A	$1 \times 10^5$ cycles
60 VDC, 1 ADC resistive	$1 \times 10^5$ cycles



**Note** Relays are field replaceable. Refer to the ***NI Switches Help*** at [ni.com/manuals](http://ni.com/manuals) for more information about replacing a failed relay.

## Physical Characteristics

Relay type	Electromechanical, non-latching
Relay contact material	Palladium-ruthenium, gold covered
Front panel connector	160 DIN 41612, 160 positions, male
<b>Power requirement</b>	
PXI Express	

12 V	24 W
3.3 V	3.6 W
Dimensions (L × W × H)	3U, one slot, PXI/cPCI module, PXI Express compatible 21.6 cm × 2.0 cm × 13.0 cm (8.5 in. × 0.8 in. × 5.1 in.)
Weight	423 g (14.9 oz)

## Environment

Maximum altitude	2,000 m (800 mbar) (at 25 °C ambient temperature)
Pollution Degree	2

Indoor use only.

### Operating Environment

Ambient temperature range	0 °C to 55 °C
Relative humidity range	10% to 90%, noncondensing

### Storage Environment

Ambient temperature range	-40 °C to 71 °C
---------------------------	-----------------



Relative humidity range	5% to 95%, noncondensing
-------------------------	--------------------------

## Shock and Vibration

Operating shock	30 g peak, half-sine, 11 ms pulse
<b>Random vibration</b>	
Operating	5 Hz to 500 Hz, 0.3 g <sub>rms</sub>
Nonoperating	5 Hz to 500 Hz, 2.4 g <sub>rms</sub>

## Compliance and Certifications

### Safety Compliance Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



**Note** For safety certifications, refer to the product label or the [Product Certifications and Declarations](#) section.

### Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions

- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



**Note** In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



**Note** Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



**Note** For EMC declarations, certifications, and additional information, refer to the [Product Certifications and Declarations](#) section.

## Product Certifications and Declarations


Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit [ni.com/product-certifications](https://ni.com/product-certifications), search by model number, and click the appropriate link.

## Environmental Management


NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the ***Engineering a Healthy Planet*** web page at [ni.com/environment](https://ni.com/environment). This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

## EU and UK Customers

-  **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit [ni.com/environment/weee](https://ni.com/environment/weee).

## 电子信息产品污染控制管理办法（中国RoHS）

-  **中国RoHS**—NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息，请登录 [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china)。(For information about China RoHS compliance, go to [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china).)