

---

# PXle-2529

# Specifications

---

2025-03-13



# Contents

PXIe-2529 Specifications ..... 3

# PXIe-2529 Specifications

This document lists specifications for the PXIe-2529. All specifications are subject to change without notice.

## PXI-2529 Specifications



**Caution** The protection provided by the PXIe-2529 can be impaired if it is used in a manner not described in this document.



**Caution** To ensure the specified EMC performance, operate this product only with shielded cables and accessories.



**Caution** Device relays might change state momentarily during electrostatic discharge.



**Caution** Refer to the ***Read Me First: Safety and Electromagnetic Compatibility*** document at [ni.com/manuals](https://ni.com/manuals) for important safety and compliance information.

## Definitions

**Warranted** specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

**Characteristics** describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the performance met by a majority of models.
- **Nominal** specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are **Warranted** unless otherwise noted.

Conditions


Specifications are valid at 23 °C unless otherwise noted.

All voltages are specified in DC, AC<sub>pk</sub>, or a combination unless otherwise specified.


Topology

Input


All input specifications are DC, AC<sub>rms</sub>, or a combination unless otherwise specified.



**Caution** This module is rated for Measurement Category I and is intended to carry signal voltages no greater than 150 V. This module can withstand up to 800 V impulse voltage. Do not use this module for connections to signals or for measurements within Measurement Categories II, III, or IV.



**Caution** Do not connect to MAINS supply circuits (e.g., wall outlets) of 115 or 230 VAC. Refer to the **Read Me First: Safety and Electromagnetic Compatibility** document for more information about Measurement Categories.



**Caution** When hazardous voltages (>42.4 V<sub>pk</sub>/60 VDC) are present on any relay terminal, safety low-voltage (≤42.4 V<sub>pk</sub>/60 VDC) cannot be connected to any other relay terminal.

Maximum switching voltage	
Channel-to-channel	150 V

Channel-to-ground	150 V, CAT I
-------------------	--------------



**Caution** The maximum switching power is limited by the maximum switching current, the maximum voltage, and must not exceed 30 W, 37.5 VA.



**Note** Switching inductive loads (for example, motors and solenoids) can produce high voltage transients in excess of the module's rated voltage. Without additional protection, these transients can interfere with module operation and impact relay life. For more information about transient suppression, visit [ni.com/info](https://ni.com/info) and enter the Info Code `induct`.

Maximum switching power (per channel)	30 W, 37.5 VA
Maximum switching current (per channel)	1 A
Maximum carry current (per channel)	2 A
Maximum module current	8 A
DC path resistance <sup>[1]</sup>	
Initial	<1 $\Omega$ , warranted
End-of-life	$\geq 2 \Omega$
Thermal EMF	<9 $\mu\text{V}$

Minimum current	10 $\mu$ A
-----------------	------------

## RF Performance

Single crosspoint bandwidth (50 $\Omega$ system, one row to one column)	>10 MHz, typical
<b>Crosstalk (50 <math>\Omega</math> system)</b>	
10 kHz	<-80 dB, typical
100 kHz	<-65 dB, typical
1 MHz	<-50 dB, typical

## Dynamic

Relay operate time <sup>[2]</sup>	4 ms, maximum, at 20 °C
Release time (at 20 °C)	4 ms, maximum, at 20 °C
<b>Expected relay life<sup>[3]</sup></b>	
Mechanical	$5 \times 10^7$ cycles

## Trigger

Input trigger <sup>[4]</sup>
------------------------------

Sources	PXI trigger lines <0...7>
Minimum pulse width	150 ns
<b>Output trigger</b>	
Destinations	PXI trigger lines <0...7>
Pulse width	Software-selectable: 1 $\mu$ s to 62 $\mu$ s
Front panel voltage	+3.3 V TTL, 8 mA, nominal

## Physical

Relay type	Electromechanical, non-latching
Relay contact material	Silver palladium and gold
I/O connector	100-pin high-density interconnect (HDI)
<b>Power requirement</b>	
PXI	6 W at 5 V 2.5 W at 3.3 V
PXI Express	7.5 W at 12 V 2.5 W at 3.3 V

Dimensions (L × W × H)	3U, one slot, PXI/cPCI module 21.6 cm × 2.0 cm × 13.0 cm (8.5 in. × 0.8 in. × 5.1 in.)
Weight	410 g (15 oz)

## Environment

Operating temperature	0 °C to 55 °C
Storage temperature	-20 °C to 70 °C
Relative humidity	5% to 85%, noncondensing
Pollution Degree	2
Maximum altitude	2,000 m

Indoor use only.

## Shock and Vibration

Operational Shock	30 g peak, half-sine, 11 ms pulse (Tested in accordance with IEC 60068-2-27. Test profile developed in accordance with MIL-PRF-28800F.)
<b>Random Vibration</b>	
Operating	5 Hz to 500 Hz, 0.3 grms



Nonoperating	5 Hz to 500 Hz, 2.4 grms (Tested in accordance with IEC 60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.)
--------------	---

## Compliance and Certifications

### Safety Compliance Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



**Note** For safety certifications, refer to the product label or the [Product Certifications and Declarations](#) section.

### Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



**Note** In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



**Note** Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



**Note** For EMC declarations, certifications, and additional information, refer to the [Product Certifications and Declarations](#) section.

## Product Certifications and Declarations


Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit [ni.com/product-certifications](https://ni.com/product-certifications), search by model number, and click the appropriate link.

## Environmental Management


NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the ***Engineering a Healthy Planet*** web page at [ni.com/environment](https://ni.com/environment). This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

## EU and UK Customers

-  **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit [ni.com/environment/weee](https://ni.com/environment/weee).

## 电子信息产品污染控制管理办法（中国RoHS）

-  **中国RoHS**—NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息，请登录 [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china)。(For information about China RoHS compliance, go to [ni.com/](https://ni.com/))

```
environment/rohs_china.)
```