
A-Code M12 to Pigtail Power and I/O Cable Pinout

2025-03-20



Contents

A-Code M12 to Pigtail Power and I/O Cable 3

A-Code M12 to Pigtail Power and I/O Cable

The A-Code M12 to Pigtail Power and I/O Cable (NI part number 145233-03) provides power to the NI ISC-178x smart camera and transmits digital I/O signals.

Figure 1. A-Code M12 to Pigtail Power and I/O Cable Pinout




Table 1. A-Code M12 to Pigtail Power and I/O Cable Wire Designations

Pin	Signal	Color	Description
1	C _{OUT}	Brown	Common reference (negative) for isolated outputs
2	Analog Out	Blue	Analog reference output for lighting controller
3	Iso Out 2+	White	General-purpose isolated output (positive)
4	V	Green	System power voltage (24 VDC \pm 10%)
5	Iso In 0	Pink	General-purpose isolated input
6	C _{IN}	Yellow	Common reference (positive or negative) for isolated inputs
7	Iso In 2	Black	General-purpose isolated input
8	Iso In 3	Gray	(NI Linux Real-Time) Reserved for safe mode (Windows) General-purpose isolated input
9	Iso In 1	Red	General-purpose isolated input
10	Iso Out 0+	Violet	General-purpose isolated output (positive)
11	C	Gray/pink	System power and analog reference common
12	Iso Out 1+	Red/blue	General-purpose isolated output (positive)

© 2017 National Instruments Corporation. All rights reserved. Refer to the <National Instruments>_Legal Information directory for information about NI copyright, patents, trademarks, warranties, product warnings, and export compliance.